



* = 1/2 STD TOLERANCE

SECTION DATA:
 $I_{xx} = 11\,446 \text{ mm}^4$
 $I_{yy} = 11\,446 \text{ mm}^4$
 Theta = 45.0
 RadGx = 6. mm
 RadGy = 6. mm
 $X_{O_{left}} = 11.1 \text{ mm}$
 $X_{O_{right}} = 11.1 \text{ mm}$
 $Y_{O_{top}} = 11.1 \text{ mm}$
 $Y_{O_{bot}} = 11.1 \text{ mm}$
 $Z_{x_{top}} = 1.030 \text{ mm}$
 $Z_{x_{bot}} = 1.030 \text{ mm}$
 $Z_{y_{left}} = 1.030 \text{ mm}$
 $Z_{y_{right}} = 1.030 \text{ mm}$

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

			B	AREA 305.6 SQ MM WEIGHT 0.828 KG M PERIMETER 102.0 MM ANOD PERIM 69.8 MM PAINT PERIM 100.0 MM C CIRCLE DIA 22. MM FACTOR 123. ALLOY 6063 TEMPER T6	 A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890	CUSTOMER G. JAMES EXTRUSION Co.		
					CUSTOMER PART NAME NO. 22.23 x 5.99 ROUND TUBE			
					SCALE 2:1	TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED		
1	12/03/99	PAD	0.25 TOL WAS 0.46 TOL C/N 3289		DRAWN	CHECK	DATE	DWG. NO.
NO	DATE	DR	REVISION		SPG		27/11/96	950-041