



* = 1/4 STD TOLERANCE

SECTION DATA:
 $I_{xx} = 8\,638\text{ mm}^4$
 $I_{yy} = 8\,638\text{ mm}^4$
 $\text{Theta} = 1.0^\circ$
 $\text{RadG}_x = 10.0\text{ mm}$
 $\text{RadG}_y = 10.0\text{ mm}$
 $\text{XC}_{\text{Right}} = 14.0\text{ mm}$
 $\text{XC}_{\text{Left}} = 14.0\text{ mm}$
 $\text{YC}_{\text{Top}} = 14.0\text{ mm}$
 $\text{YC}_{\text{Bot}} = 14.0\text{ mm}$
 $Z_{xx\text{Top}} = 616\text{ mm}^3$
 $Z_{xx\text{Bot}} = 616\text{ mm}^3$
 $Z_{yy\text{Right}} = 616\text{ mm}^3$
 $Z_{yy\text{Left}} = 616\text{ mm}^3$

0.40 RADIUS ON ALL OUTSIDE CORNERS
 UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

		A				G. JAMES EXTRUSION Co.	
						28.05 DIA. x 1.125 TUBE	
						2:1	
1	06/03/01	SPG	ALLOY & TEMPER WERE 6063 T5	95.2		PAD	01/03/01
				0.258			950-072
				169.2			
				88.1			
				100.0 (0.0)			
				28.			
				656.			
				606391			
				T6			