



SECTION DATA:
 $I_{xx} = 37\,063 \text{ mm}^4$
 $I_{yy} = 37\,063 \text{ mm}^4$
 Theta = 1.0
 RadGx = 13. mm
 RadGy = 13. mm
 $X_{O_{left}} = 19.1 \text{ mm}$
 $X_{O_{right}} = 19.1 \text{ mm}$
 $Y_{O_{top}} = 19.1 \text{ mm}$
 $Y_{O_{bot}} = 19.1 \text{ mm}$
 $Z_{x_{top}} = 1\,946 \text{ mm}$
 $Z_{x_{bot}} = 1\,946 \text{ mm}$
 $Z_{y_{left}} = 1\,946 \text{ mm}$
 $Z_{y_{right}} = 1\,946 \text{ mm}$

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

			A	AREA 226.8 SQ MM WEIGHT 0.615 KG M PERIMETER 226.8 MM ANOD PERIM 119.7 MM PAINT PERIM 119.7 MM C CIRCLE DIA 38. MM FACTOR 369. ALLOY 6063 TEMPER T6	 A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890	CUSTOMER G. JAMES EXTRUSION Co.	
					CUSTOMER PART NAME NO. 38.10 x 2.0 ROUND TUBE		
					SCALE 2:1	TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED	
NO	DATE	DR	REVISION		DRAWN SPG	CHECK DATE 15/06/95	DWG. NO. 950-107