


SECTION DATA:
 $I_{xx} = 43\,216 \text{ mm}^4$
 $I_{yy} = 43\,216 \text{ mm}^4$
 $\text{Theta} = 1.0^\circ$
 $\text{RadG}_x = 13. \text{ mm}$
 $\text{RadG}_y = 13. \text{ mm}$
 $X_{\text{Cleft}} = 20.0 \text{ mm}$
 $X_{\text{Cright}} = 20.0 \text{ mm}$
 $Y_{\text{Ctop}} = 20.0 \text{ mm}$
 $Y_{\text{Cbot}} = 20.0 \text{ mm}$
 $Z_{xx\text{top}} = 2\,161 \text{ mm}^3$
 $Z_{xx\text{bot}} = 2\,161 \text{ mm}^3$
 $Z_{yy\text{left}} = 2\,161 \text{ mm}^3$
 $Z_{yy\text{right}} = 2\,161 \text{ mm}^3$

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

| | | | | | | | | | | | | | | | |
|----|------|----|----------|---|--|--------------|-------|-------|---|-----------------------|--|--|--|--|--|
| | | | | A | | AREA | 238.8 | SQ MM |  A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890 | CUSTOMER | | | G. JAMES EXTRUSION Co. | | |
| | | | | | | WEIGHT | 0.647 | KG M | | CUSTOMER PART NAME | | | NO. | | |
| | | | | | | PERIMETER | 238.8 | MM | | 40.0 x 2.0 ROUND TUBE | | | | | |
| | | | | | | ANOD PERIM | 125.7 | MM | | SCALE | | | TOLERANCES IN ACCORDANCE WITH AS 1866-1986 | | |
| | | | | | | PAINT PERIM | 125.7 | MM | | 1:1 | | | APPLY UNLESS OTHERWISE SPECIFIED | | |
| | | | | | | C CIRCLE DIA | 40. | MM | | DRAWN | | | DATE | | |
| | | | | | | FACTOR | 369. | | | JWC | | | 06/04/87 | | |
| | | | | | | ALLOY | 6063 | | | CHECK | | | DWG. NO. | | |
| | | | | | | TEMPER | T6 | | | | | | 950-112 | | |
| NO | DATE | DR | REVISION | | | | | | | | | | | | |