


SECTION DATA:
 $I_x = 123\,718 \text{ mm}^4$
 $I_y = 123\,718 \text{ mm}^4$
 Theta = 0.
 RadG_x = 16. mm
 RadG_y = 16. mm
 XO_{Left} = 24.0 mm
 XC_{Right} = 24.0 mm
 YO_{Top} = 24.0 mm
 YO_{Bot} = 24.0 mm
 Z_{xTop} = 5.166 mm
 Z_{xBot} = 5.166 mm
 Z_{yLeft} = 5.166 mm
 Z_{yRight} = 5.166 mm

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

NO	DATE	DR	REVISION
			A

AREA	501.0	SQ MM
WEIGHT	1.358	KG M
PERIMETER	278.3	MM
ANOD PERIM	150.5	MM
PAINT PERIM	150.5	MM
C CIRCLE DIA	48.	MM
FACTOR	205.	
ALLOY	6063	
TEMPER	T6	



G. James Extrusion Co.
 A.C.N 010 828 234
 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009
 PO BOX 1376, EAGLE FARM BC, 4009
 PHONE : (07) 3877 2833 FAX : (07) 3877 2890

CUSTOMER G. JAMES EXTRUSION Co.			
CUSTOMER PART NAME 47.9 x 3.6 ROUND TUBE		NO.	
SCALE 2:1	TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED		
DRAWN SPG	CHECK	DATE 27/09/94	DWG. NO. 950-146