



\* = 1/4 STD TOLERANCE

TOTAL SURFACE EXPOSED

SECTION DATA:  
 $I_{xx} = 116\,513 \text{ mm}^4$   
 $I_{yy} = 116\,513 \text{ mm}^4$   
 Theta = 0.  
 RadG<sub>x</sub> = 17. mm  
 RadG<sub>y</sub> = 17. mm  
 X<sub>C</sub><sub>Right</sub> = 25.4 mm  
 X<sub>C</sub><sub>Left</sub> = 25.4 mm  
 Y<sub>C</sub><sub>Top</sub> = 25.4 mm  
 Y<sub>C</sub><sub>Bot</sub> = 25.4 mm  
 Z<sub>xx</sub><sub>top</sub> = 4 583 mm  
 Z<sub>xx</sub><sub>bot</sub> = 4 583 mm  
 Z<sub>yy</sub><sub>right</sub> = 4 583 mm  
 Z<sub>yy</sub><sub>left</sub> = 4 583 mm

0.40 RADIUS ON ALL OUTSIDE CORNERS  
 UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : STRUCTURAL

1	07/06/01	PAD	+/- 0.23 1/4 STD WAS +/- 0.40 1/2 STD	A	399.8 1.084 302.9 159.7 159.7 (0.0) 51. 280. 6351 T5	G. JAMES EXTRUSION Co.			
						50.85 x 2.64 ROUND TUBE			
		1:1							
		SPG		11/05/01		950-191			