



* = 1/2 STD TOLERANCE

NO EXPOSED SURFACE

SECTION DATA:
 $I_{XX} = 3\,123\,166 \text{ mm}^4$
 $I_{YY} = 3\,123\,166 \text{ mm}^4$
 $\text{Theta} = 1.0^\circ$
 $\text{RadG}_x = 43. \text{ mm}$
 $\text{RadG}_y = 43. \text{ mm}$
 $X_{\text{Right}} = 63.5 \text{ mm}$
 $X_{\text{Left}} = 63.5 \text{ mm}$
 $Y_{\text{Top}} = 63.5 \text{ mm}$
 $Y_{\text{Bot}} = 63.5 \text{ mm}$
 $Z_{xx\text{top}} = 49\,184 \text{ mm}^3$
 $Z_{xx\text{bot}} = 49\,184 \text{ mm}^3$
 $Z_{yy\text{right}} = 49\,184 \text{ mm}^3$
 $Z_{yy\text{left}} = 49\,184 \text{ mm}^3$

0.40 RADIUS ON ALL OUTSIDE CORNERS
 UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : STRUCTURAL

			A			G. JAMES EXTRUSION Co.		
				1657.5		127 x 4.30 ROUND TUBE		
				4.492		1:1		
				770.9		SPG	13/09/00	950-477
				399.0				
				399.0 (0.0)				
				127.				
				172.				
				6351				
				T5				