



DNV CERTIFICATION REQUIRED

= 3/4 STANDARD TOLERANCE

TOTAL SURFACE EXPOSED

SECTION DATA:

 $I_{xx} = 7\,405\,651\text{ mm}^4$ $I_{yy} = 7\,405\,651\text{ mm}^4$ Theta = 58° RadG_x = 52 mmRadG_y = 52 mmXC_{Right} = 76.2 mmXC_{Left} = 76.2 mmYC_{top} = 76.2 mmYC_{bot} = 76.2 mmZ_{xx}_{top} = 97 187 mm³Z_{xx}_{bot} = 97 187 mm³Z_{yy}_{right} = 97 187 mm³Z_{yy}_{left} = 97 187 mm³0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : STRUCTURAL

A 47872

AREA	2759.6	SQ MM
WEIGHT	7.478	KG M
PERIMETER	919.9	MM
ANOD PERIM	478.8	MM
PAINT PERIM	478.8 (0.0)	MM
C CIRCLE DIA	152	MM
FACTOR	123	
ALLOY	NV6082	
TEMPER	T6	

G. James
Extrusion Co.

A.C.N 010 828 234
1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009
PO BOX 1376, EAGLE FARM BC, 4009
PHONE : (07) 3877 2833 FAX : (07) 3877 2890

© COPYRIGHT 2004
THIS DRAWING IS THE PROPERTY OF
G.JAMES EXTRUSION CO. PTY LTD
ALL RIGHTS RESERVED

CUSTOMER

G. JAMES EXTRUSION Co.

CUSTOMER PART NAME

NO.

DIA 152.40 x 6.0 ROUND TUBE

SCALE

1:1

TOLERANCES IN ACCORDANCE WITH AS/NZS 1866:1997
APPLY UNLESS OTHERWISE SPECIFIED

DRAWN

SPG

CHECK

DATE

30/06/05

DWG. NO.

950-505

NO	DATE	DR	REVISION