



SECTION DATA:  
I<sub>xx</sub> = 39 728 mm<sup>4</sup>  
I<sub>yy</sub> = 39 728 mm<sup>4</sup>  
Theta = 45.0°  
RadG<sub>x</sub> = 16. mm  
RadG<sub>y</sub> = 16. mm  
X<sub>Qleft</sub> = 36.9 mm  
X<sub>Qright</sub> = 13.1 mm  
Y<sub>Qtop</sub> = 36.9 mm  
Y<sub>Qbot</sub> = 13.1 mm  
Z<sub>xx</sub>top = 1 077 mm<sup>3</sup>  
Z<sub>xx</sub>bot = 3 033 mm<sup>3</sup>  
Z<sub>yy</sub>left = 1 077 mm<sup>3</sup>  
Z<sub>yy</sub>right = 3 033 mm<sup>3</sup>

1.60 TYP WALL THICKNESS  
UNLESS OTHERWISE SPECIFIED

0.40 RADIUS ON ALL OUTSIDE CORNERS  
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

				AREA	157.4	SQ MM	<div><div></div><div>G. James Extrusion Co.</div><div>A.C.N 010 828 234</div><div>1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009</div><div>PO BOX 1376, EAGLE FARM BC, 4009</div><div>PHONE : (07) 3877 2833 FAX : (07) 3877 2890</div></div>	CUSTOMER			
				WEIGHT	0.427			G. JAMES EXTRUSION			
NO	DATE	DR	REVISION	PERIMETER	200.0	MM		CUSTOMER PART NAME NO.			
				ANOD PERIM	200.0	MM		50 x 50 x 1.6 ANGLE			
				PAINT PERIM	200.0	MM		SCALE			
				C CIRCLE DIA	71.	MM		2:1		TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED	
				FACTOR	469.			DRAWN	CHECK	DATE	DWG. NO.
				ALLOY	6063						
				TEMPER	T6			SPG		02/06/94	900-070