



TOTAL SURFACE EXPOSED

SECTION DATA:
 $I_{xx} = 41\,867 \text{ mm}^4$
 $I_{yy} = 167\,327 \text{ mm}^4$
 $\text{Theta} = 71.0^\circ$
 $\text{RadG}_x = 11. \text{ mm}$
 $\text{RadG}_y = 23. \text{ mm}$
 $X_{\text{Right}} = 46.6 \text{ mm}$
 $X_{\text{Left}} = 23.4 \text{ mm}$
 $Y_{\text{Top}} = 31.6 \text{ mm}$
 $Y_{\text{Bot}} = 8.4 \text{ mm}$
 $Z_{yy\text{top}} = 1\,326 \text{ mm}$
 $Z_{xx\text{bot}} = 4\,975 \text{ mm}$
 $Z_{yy\text{right}} = 3\,592 \text{ mm}$
 $Z_{yy\text{left}} = 7\,146 \text{ mm}$

0.40 RADIUS ON ALL OUTSIDE CORNERS
 UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

| | | | | | | | | | |
|--|--|--|--|--|--|------------------------|--|----------|---------|
| | | | | 321.0 0.870 220.0 220.0 220.0 (0.0) 81. 253. 6063 T6 | | G. JAMES EXTRUSION Co. | | | |
| | | | | | | 70 x 40 x 3 ANGLE | | | |
| | | | | | | 1:1 | | | |
| | | | | | | PAD | | 16/07/01 | 901-215 |