



SECTION DATA:  
 $I_{xx} = 5\,757 \text{ mm}^4$   
 $I_{yy} = 5\,410 \text{ mm}^4$   
 Theta = 0.0  
 RadG<sub>x</sub> = 6. mm  
 RadG<sub>y</sub> = 6. mm  
 X<sub>Right</sub> = 8.0 mm  
 X<sub>Left</sub> = 8.0 mm  
 Y<sub>Top</sub> = 11.7 mm  
 Y<sub>Bot</sub> = 8.3 mm  
 Z<sub>xxTop</sub> = 492 mm<sup>3</sup>  
 Z<sub>xxBot</sub> = 694 mm<sup>3</sup>  
 Z<sub>yyRight</sub> = 676 mm<sup>3</sup>  
 Z<sub>yyLeft</sub> = 676 mm<sup>3</sup>

0.40 RADIUS ON ALL OUTSIDE CORNERS  
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

NO	DATE	DR	REVISION

AREA	150.0	SQ MM
WEIGHT	0.407	KG M
PERIMETER	106.0	MM
ANOD PERIM	106.0	MM
PAINT PERIM	106.0 (0.0)	MM
C CIRCLE DIA	26.	MM
FACTOR	261.	
ALLOY	6063	
TEMPER	T6	



A.C.N 010 828 234  
 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009  
 PO BOX 1376, EAGLE FARM BC, 4009  
 PHONE : (07) 3877 2833 FAX : (07) 3877 2890

CUSTOMER G. JAMES EXTRUSION Co.			
CUSTOMER PART NAME 16 x 20 x 3 CHANNEL		NO.	
SCALE 2:1		TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED	
DRAWN PAD	CHECK	DATE 30/08/99	DWG. NO. 910-018