



SECTION DATA:
 $I_{xx} = 19\,237 \text{ mm}^4$
 $I_{yy} = 85\,383 \text{ mm}^4$
 Theta = 1.0
 RadG_x = 10. mm
 RadG_y = 20. mm
 X_{Qleft} = 25.0 mm
 X_{Qright} = 25.0 mm
 Y_{Qtop} = 21.1 mm
 Y_{Qbot} = 8.9 mm
 Z_{xx top} = 913 mm³
 Z_{xx bot} = 2 156 mm³
 Z_{yy left} = 3 415 mm³
 Z_{yy right} = 769 mm³

0.40 RADIUS ON ALL OUTSIDE CORNERS
 UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

			AREA	212.0	SQ MM
			WEIGHT	0.575	KG M
			PERIMETER	216.0	MM
			ANOD PERIM	216.0	MM
			PAINT PERIM	216.0	MM
			C CIRCLE DIA	58.	MM
			FACTOR	376.	
			ALLOY	6063	
			TEMPER	T6	



A.C.N 010 828 234
 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009
 PO BOX 1376, EAGLE FARM BC, 4009
 PHONE : (07) 3877 2833 FAX : (07) 3877 2890

CUSTOMER			
G. JAMES EXTRUSION Co.			
CUSTOMER PART NAME		NO.	
50 x 30 x 2 CHANNEL			
SCALE		TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED	
2:1			
DRAWN	CHECK	DATE	DWG. NO.
SPG		12/05/95	910-103