



SECTION DATA:
 $I_{xx} = 3\,333 \text{ mm}^4$
 $I_{yy} = 53\,333 \text{ mm}^4$
 Theta = 1.0
 RadG_x = 3. mm
 RadG_y = 12. mm
 X_{Left} = 20.0 mm
 X_{Right} = 20.0 mm
 Y_{Top} = 5.0 mm
 Y_{Bot} = 5.0 mm
 Z_{x top} = 667 mm³
 Z_{x bot} = 667 mm³
 Z_{y left} = 2 667 mm³
 Z_{y right} = 167 mm³

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

			AREA 400.0 SQ MM WEIGHT 1.084 KG M PERIMETER 100.0 MM ANOD PERIM 100.0 MM PAINT PERIM 100.0 MM C CIRCLE DIA 41. MM FACTOR 92. ALLOY 6063 TEMPER T6	 A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890	CUSTOMER G. JAMES EXTRUSION Co.		
					CUSTOMER PART NAME NO. 40 x 10 FLAT BAR		
				SCALE 2:1	TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED		
NO	DATE	DR	REVISION	DRAWN SPG	CHECK SPG	DATE 23/05/96	DWG. NO. 920-082