



SECTION DATA:
 $I_{xx} = 2\,491\text{ mm}^4$
 $I_{yy} = 2\,491\text{ mm}^4$
 $\text{Theta} = 1.0$
 $\text{RadG}_x = 5.0\text{ mm}$
 $\text{RadG}_y = 5.0\text{ mm}$
 $X_{\text{Left}} = 7.50\text{ mm}$
 $X_{\text{Right}} = 7.50\text{ mm}$
 $Y_{\text{Top}} = 7.50\text{ mm}$
 $Y_{\text{Bot}} = 7.50\text{ mm}$
 $Z_{xx\text{top}} = 332\text{ mm}^3$
 $Z_{xx\text{bot}} = 332\text{ mm}^3$
 $Z_{yy\text{left}} = 332\text{ mm}^3$
 $Z_{yy\text{right}} = 332\text{ mm}^3$

a = 1.60 radius

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

			A	AREA 83.6 SQ MM WEIGHT 0.226 KG M PERIMETER 104.5 MM ANOD PERIM 57.3 MM PAINT PERIM 100.0 MM C CIRCLE DIA 20. MM FACTOR 461. ALLOY 6063 TEMPER T6	 A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890	CUSTOMER G. JAMES EXTRUSION Co.		
					CUSTOMER PART NAME NO. 15 x 1.6 SQUARE BOX RAD CNRS			
					SCALE 2:1	TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED		
NO	DATE	DR	REVISION		DRAWN SPG	CHECK	DATE 13/04/95	DWG. NO. 931-007