



TOTAL SURFACE EXPOSED

SECTION DATA:
 $I_{xx} = 52\,514 \text{ mm}^4$
 $I_{yy} = 350\,814 \text{ mm}^4$
 Theta = 1.0
 RadG_x = 10. mm
 RadG_y = 27. mm
 X_CRight = 40.0 mm
 X_CLeft = 40.0 mm
 Y_Ctop = 12.5 mm
 Y_Cbot = 12.5 mm
 Z_{xx}top = 4 201 mm³
 Z_{xx}bot = 4 201 mm³
 Z_{yy}right = 8 770 mm³
 Z_{yy}left = 8 770 mm³

2.40 ±0.25 TYP WALL THICKNESS
UNLESS OTHERWISE SPECIFIED

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

			A	AREA 481.0 SQ MM WEIGHT 1.303 KG M PERIMETER 400.8 MM ANOD PERIM 210.0 MM PAINT PERIM 210.0 MM C CIRCLE DIA 84. MM FACTOR 308. ALLOY 6063 TEMPER T5	 A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890	CUSTOMER G. JAMES EXTRUSION Co.		
						CUSTOMER PART NAME NO. 80 x 25 x 2.40 RECT. BOX		
						SCALE 1:1	TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED	
NO	DATE	DR	REVISION			DRAWN SPG	CHECK DATE 10/05/99	DWG. NO. 940-081