



SECTION DATA:
 $I_{xx} = 24\,375 \text{ mm}^4$
 $I_{yy} = 72\,868 \text{ mm}^4$
 Theta = 1.0
 RadG_x = 10. mm
 RadG_y = 18. mm
 XQ_{Left} = 25.00 mm
 XQ_{Right} = 25.00 mm
 YQ_{Top} = 12.50 mm
 YQ_{Bot} = 12.50 mm
 Z_{xx}_{top} = 1 950 mm³
 Z_{xx}_{bot} = 1 950 mm³
 Z_{yy}_{left} = 2 915 mm³
 Z_{yy}_{right} = 975 mm³

a = 1.60 radius
 0.40 RADIUS ON ALL OUTSIDE CORNERS
 UNLESS OTHERWISE SPECIFIED
 EXTRUDED FINISH : ARCHITECTURAL

			A	AREA 227.6 SQ MM WEIGHT 0.617 KG M PERIMETER 284.5 MM ANOD PERIM 147.3 MM PAINT PERIM 147.3 MM C CIRCLE DIA 55. MM FACTOR 461. ALLOY 6063 TEMPER T6	 A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890	CUSTOMER G. JAMES EXTRUSION Co.		
						CUSTOMER PART NAME NO. 50 x 25 x 1.60 RECT. BOX R/C		
					SCALE 2:1	TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED		
NO	DATE	DR	REVISION		DRAWN SPG	CHECK	DATE 18/12/96	DWG. NO. 941-232