



ACTUAL SIZE
NO EXPOSED SURFACE

* = 1/2 STD TOLERANCE

SECTION DATA:
 $I_{xx} = 19\,175 \text{ mm}^4$
 $I_{yy} = 19\,175 \text{ mm}^4$
 Theta = 1.0°
 RadGx = 6. mm
 RadGy = 6. mm
 XQ_{Right} = 12.5 mm
 XQ_{Left} = 12.5 mm
 YQ_{Top} = 12.5 mm
 YQ_{Bot} = 12.5 mm
 $Z_{xx}^{\text{top}} = 1\,534 \text{ mm}^3$
 $Z_{xx}^{\text{bot}} = 1\,534 \text{ mm}^3$
 $Z_{yy}^{\text{right}} = 1\,534 \text{ mm}^3$
 $Z_{yy}^{\text{left}} = 1\,534 \text{ mm}^3$

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : STRUCTURAL

1	03/07/01	SPG	1/2 STANDARD TOLERANCE ADDED C/N 4308	490.9 1.330 78.5 78.5 100.0 (0.0) 25. 59. 6351 T6	G. JAMES EXTRUSION Co.			
					25mm ROUND SOLID			
					2:1			
					RB		02/11/89	960-055