



TOTAL SURFACE EXPOSED

SECTION DATA:  
 $I_{xx} = 103\,436 \text{ mm}^4$   
 $I_{yy} = 103\,436 \text{ mm}^4$   
 Theta = 0.  
 RadG<sub>x</sub> = 10. mm  
 RadG<sub>y</sub> = 10. mm  
 XQ<sub>Right</sub> = 19.1 mm  
 XQ<sub>Left</sub> = 19.1 mm  
 YQ<sub>Top</sub> = 19.1 mm  
 YQ<sub>Bot</sub> = 19.1 mm  
 Z<sub>xx</sub><sub>top</sub> = 5 430 mm  
 Z<sub>xx</sub><sub>bot</sub> = 5 430 mm  
 Z<sub>yy</sub><sub>right</sub> = 5 430 mm  
 Z<sub>yy</sub><sub>left</sub> = 5 430 mm

0.40 RADIUS ON ALL OUTSIDE CORNERS  
 UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

				1140.1 3.090 119.7 119.7 119.7 (0.0) 38. 39. 6063 T5		G. JAMES EXTRUSION Co.			
						DIA 38.10 ROUND SOLID ROD			
						1:1			
						A.T		03/11/00	960-150