



NO EXPOSED SURFACE

MOMENTS OF INERTIA:

$$I_{xx} = 132\,093 \text{ mm}^4$$

$$I_{yy} = 63\,603 \text{ mm}^4$$

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : STRUCTURAL

NO	DATE	DR	REVISION	AREA 579.5 SQ MM WEIGHT 1.570 KG M PERIMETER 194.8 MM ANOD PERIM 194.8 MM PAINT PERIM 194.8 (0.0) MM C CIRCLE DIA 63 MM FACTOR 124 ALLOY 6351 TEMPER T5	 <p>© COPYRIGHT 2004 THIS DRAWING IS THE PROPERTY OF G. JAMES EXTRUSION CO. PTY LTD ALL RIGHTS RESERVED</p> <p>A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890</p>	CUSTOMER G. JAMES EXTRUSION Co.	
				CUSTOMER PART NAME NO. 50 x 50 x 6.0 'T' SECTION R/C		SCALE 1:1	TOLERANCES IN ACCORDANCE WITH AS/NZS 1866:1997 APPLY UNLESS OTHERWISE SPECIFIED
				DRAWN SPG	CHECK	DATE 23/01/97	DWG. NO. 970-103